H-40/80



H-40/60

STANDARD FEATURES:

- 20 HP motor
- 3" blade
- Power rollers
- Carbide guides
- · Hydraulic driven blade brush
- Hydraulic blade tensioning
- Up to 80" capacity
- Flood coolant
- · Wash down hose

OPTIONS:

- Outboard vise
- · Laser beam light
- · Variable vise pressure
- · Mist coolant system

MATERIAL HANDLING:

5' or 10' Powered Conveyors



- Blade Drive
- Descent Meter
- 3 HP Hydraulic Drive
- 2 1/1" Blade
- 12° Canted Head
- Hydraulic Guide Arm Positioning
- Carbide Guide Inserts

Hydraulic System

- 4" Hydraulic Driven Blade Brush
- Hydraulic Blade Tensioning

- Blade Breakage Switch
- Chip Auger
- Flood Coolant
- Wash Down Hose

OPTIONS:

- Hydraulic Overhead Clamp
- · Laser Beam Light
- Outboard Vise
- Mist coolant system

Large Band Wheels

Constructed from heavy cast iron, the Band Wheels are canted creating less blade twist resulting in longer blade life.

Note: Photos may show optional equipment.

Powered Rollers

8' variable frequency drive controlled power rollers through the base of the saw (40/40, 40/60, & 40/80



Hydraulic system controls all vising, head up/down, blade

tension, guide arm and shuttle. Conveniently located in a

"swing out" compartment for easy access and enhanced



