

VW-18

Photos may show optional equipment.



OPTIONAL POWER TILT

Allows the operator to enter a desired angle up to 60° in either direction and have the machine automatically move the head to that angle. This option features an upgraded control, as pictured below.

ADJUSTABLE CANTED HEAD

The machine is capable of cutting with the saw head at 90° or with a 3° cant. Minimizes chip load resulting in a more efficient, quicker cut and longer blade life.



STANDARD FEATURES

- Adjustable 3° canted head
- Semi-automatic control
- Two full stroking hydraulic vises
- Manual precise head positioning from
- 60° left to 60° right
- Digital angle display
- Mechanically adjustable idler side guide arm
- On-demand hydraulics save energy
- 5 HP VFD. True direct blade drive
- Hydraulic positive down feed
- Cast iron band wheels
- Replaceable blade brush
- Robust steel base
- Easy access electrical panel and hydraulics
- Blade breakage switch
- Mechanical band tensioning with digital readout
- Replaceable carbide guide inserts
- 0.5 HP hydraulic pump provides

- system pressure
- Safety door interlocks
- Flood coolant with wash down hose
- Laser light and work light

OPTIONAL FEATURES

- Power tilt
- Chip bucket
- Hydraulic overhead bundling
- Mist lubrication
- Work stop
- Tall square vise inserts
- Variable vise pressure
- Power transformer
- Idler conveyors