## CE50H3 Angle Roll

Hydraulic Angle Roll • Section Bender



ERCOLIN



Operating Position



Universal Tooling Set Included for Multiple Profiles



# **Hydraulic Downfeed Improves Productivity**

#### **FEATURES**

- Universal tooling set included with each machine
- Forged roll shafts precision ground and fitted for maximum performance and minimal deflection
- Roll shafts supported with conical steel bearings on each side of A Frame
- Heavy duty structure and rigid components for high section modulus ratings
- Reinforced engineered mainframe design proven to outperform competitive models
- In-line direct drive roll shaft system 3-roll driven

- Threaded roll shafts with micrometric flange adjustment helps eliminate spacer usage
- Touchpad controls with digital center roll positioning
- Control tower with low voltage controls and foot pedal
- Hydraulic machine with memory storage has eight (8) individual programs and unlimited passes
- Patented by Ercolina, simultaneous downfeed and roll movement minimizes deformation
- Optional anti-twist correction system required for angle iron "Leg In" applications

### **CE50H3 Capacities & Specifications**

Pipe (Max.)	2½" Sch. 40
Angle (Max.)	2½" x 2½" x ½"
Tube (Max.)	3" – .095 wall
Roll Shaft Diameter	50mm
Center Roll Positioning	Hydraulic 10 Tons
Shaft Speed	9 RPM
Universal Tooling (Included)	7" O.D.
Programming	NC - Touchpad
Number of Programs	8
Distance between Shafts	1111/8"
Operating Voltage	220V or 480V 3ph
Length, Width, Height	45" x 29" x 52"

All capacities based on mild grade materials; heavy wall and high tensile materials reduce machine capacity.

### **POPULAR ACCESSORIES**



Spray Lubricant



**Small Radius Tooling** 



Pipe & Tube Tooling



Radius & Degree Measuring Kit



Anti-Twist Device

Minimum Radius Guide Pages 72-73

**Tooling Sets Pages 74-76** 

**Accessories Pages 77-80** 



Ercolina Bending Application

Product
Demonstrations
Available on Website

NEED ADDITIONAL HELP? CONTACT ERCOLINA:

563.391.7700

info@ercolina-usa.com

ercolina-usa.com