True Swivel Head Miters to 60° 13" Capacity

Table 13165 Miter Head Bandsaw





Model 13165 Miter Head Bandsaw



Standard Features

Saw Head Swivels on Precision Ball Bearings

Miter to 60° - No Need to Swivel the Stock

Large Protractor for Accurate Angle Selection

5' x 18" Infeed Roller Conveyor

Spring-Loaded Carbide Guides with Rollers

Combination Reduction Gearbox and Ring & Pinion Blade Drive

Baldor® Motor

3hp Motor 3 Phase TEFC 2hp Single Phase ODP

Infinitely Variable Blade Speeds

Variable Hydraulic Downfeed Control

Work Light with Transformer

Rite-Tension® Blade Tensioning Device

Wet Cutting System with Full Surround Pan

Powered Blade Brush

110 Volts at Controls

Magnetic Starter with Overload and Undervoltage Protection

Precision Ground Bed and Vise Jaws

Quick Acting Vise

Adjustable Stock Stop/Back Gauge

Auto Shut-Off at End of Cut

OSHA Blade Guarding

Tiger-Tooth® Bi-Metal Blade

Coolant for Initial Start-Up

Specifications

Capacity @ 0° (90°) @ 45° @ 60°	Round Rectangular 13" 13"H x 16"W 11-1/2" 13"H x 11-1/2"W 8" 8-1/2"H x 8"W
Blade Size	1" x .035" x 12'6" (150")
Blade Speeds	Infinitely Variable 70-375 SFPM
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	115-208-230/60/1 208-230-460/60/3
Coolant System	Tank Capacity 8 Gallons Submersible Pump 115V/.6 Amp/3 GPM
Vise Control	Quick Acting/Manual Screw
Feed Rate Control	Variable Hydraulic
Band Wheels	15" Diameter Cast Iron
Stock Stop Projection	25"
Bed Height	35"
Floor Area	90"W x 76"L
Shipping Weight	1600 Lbs.

Available Factory Installed Options

PLC Controlled Semi-Automatic Operation

Blade Break/Stall Switch

Flush Hose with 8.5 GPM Pump

Powered Frame Raise and/or Powered Vise

Laser Line Pointer

Casters (Set of 4, 2 Locking)

NFPA Electrics (with Disconnect)

Stock Stand, 18"

5' Non-Powered Roller Conveyor

10' Non-Powered Conveyors

Please Contact Our Factory for Additional Options

