



## Technical Data



TYPES	Capacity		Cutting Length	Rake Angle	Main Motor	Working Pressure	Number of Hold-downs	Strokes per Minute	Capacity of Oil Tank	Back-gauge Range	Back-gauge Motor	Approx. Weight
	≤450 N/mm <sup>2</sup>	≤700 N/mm <sup>2</sup>										
	mm	mm										
<b>HNC 3106</b>	6	4	3070	0.5°-1.5°	11	260	16	20-32	240	1000	0.37	7800
<b>HNC 3110</b>	10	6	3070	0.5°-2.0°	22	260	15	12-18	360	1000	0.37	11000
<b>HNC 3113</b>	13	8	3070	0.5°-2.5°	30	260	15	9-14	360	1000	0.37	13000
<b>HNC 3116</b>	16	10	3070	0.5°-3.0°	30	260	15	8-14	400	1000	0.55	16500
<b>HNC 3120</b>	20	13	3070	0.5°-3.0°	37	260	16	6-10	400	1000	0.55	21000
<b>HNC 3125</b>	25	16	3070	0.5°-3.5°	45	260	15	4-6	600	1000	0.55	23000
<b>HNC 4106</b>	6	4	4070	0.5°-1.5°	11	260	21	16-25	360	1000	0.55	12000
<b>HNC 4110</b>	10	6	4070	0.5°-2.0°	22	260	21	9-14	360	1000	0.55	15000
<b>HNC 4113</b>	13	8	4070	0.5°-2.5°	30	260	21	7-14	400	1000	0.55	18000
<b>HNC 4116</b>	16	10	4070	0.5°-3.0°	30	260	21	7-12	400	1000	0.55	23500
<b>HNC 4120</b>	20	13	4070	0.5°-3.0°	37	260	21	6-9	400	1000	0.55	26000
<b>HNC 6106</b>	6	4	6070	0.5°-2.0°	18.5	260	30	12-18	360	1000	0.55	22000
<b>HNC 6110</b>	10	6	6070	0.5°-2.0°	22	260	30	6-10	400	1000	0.55	30000
<b>HNC 6113</b>	13	8	6070	0.5°-2.5°	30	260	30	6-10	400	1000	0.75	38000
<b>HNC 6116</b>	16	10	6070	0.5°-3.0°	37	260	30	5-9	400	1000	0.75	43000
<b>HNC 6120</b>	20	13	6070	0.5°-3.0°	37	260	30	5-9	600	1000	0.75	48000



Machines built with CE-safety conformity are available as option.  
Design and specifications are subject to change without notice.