

TECHNICAL DATA

		1254x40	2104x60	2606x90	3104x90	3106x120	3108x160	3110x200	3112x240	3116x300	3120x440	4106x160	4108x200	4110x240	4112x300	4116x440	6106x240	6108x300	6110x380	6112x440	6116x600
Capacity	kN	400	600	900	900	1200	1600	2000	2400	3000	4400	1600	2000	2400	3000	4400	2400	3000	3800	4400	6000
Motor Output	kW	4	5,5	7.5	7.5	11	15	19	22	22	30	15	18,5	22	22	30	22	22	30	30	37
Oil Tank Volume	Lt	80	140	140	140	140	210	210	210	280	450	210	210	210	280	450	300	300	450	450	500
Speeds (mm/s)	Approach	160	150	150	160	160	160	150	130	110	80	170	160	150	120	80	140	120	90	90	80
	Working	10	10	10	10	10	10	10	10	8	8	10	10	10	8	8	10	8	8	8	7
	Return	130	130	130	130	130	130	130	120	100	70	120	110	100	90	70	100	70	70	70	70
Approx. Weight	Ton	3.3	5.4	7.1	7.9	8.4	9.7	10	11	15	22	12	12.5	14	18.5	26	25	30	35	39	55
Bending Length	A mm	1250	2100	2600	3100	3100	3100	3100	3100	3100	3100	4100	4100	4100	4100	4100	6100	6100	6100	6100	6100
Inside Frames	B mm	1070	1600	2050	2550	2550	2550	2550	2550	2550	2550	3550	3550	3550	3550	3550	5100	5100	5100	5100	5100
Side Frame Width	C mm	1470	1580	1580	1590	1590	1600	1600	1610	1815	2060	1600	1600	1610	1820	2235	1960	2060	2210	2250	2400
Bed Height	G mm	800	880	880	880	880	880	880	880	905	1005	880	880	880	980	955	1100	1115	1100	1100	1050
Daylight Opening	K mm	455	475	540	530	540	540	530	530	660	575	530	530	530	635	590	500	560	570	570	620
Stroke	L mm	215	210	260	260	260	260	260	260	320	320	260	260	260	320	320	260	320	320	320	360
Table Width	M mm	60	60	60	60	60	60	90	90	380	450	60	90	90	280	380	90	200	240	280	380
Throat Gap	N mm	410	410	410	410	410	410	410	410	500	500	410	410	410	500	500	500	500	500	500	500

• Design and specifications are subject to change without notice