

TECHNICAL DATA

| | | 1254x40 | 2104x60 | 2606x90 | 3104x90 | 3106x120 | 3108x160 | 3110x200 | 3112x240 | 3116x300 | 3120x440 | 4106x160 | 4108x200 | 4110x240 | 4112x300 |
|------------------|----------|---------|---------|---------|---------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Capacity | kN | 400 | 600 | 900 | 900 | 1200 | 1600 | 2000 | 2400 | 3000 | 4400 | 1600 | 2000 | 2400 | 3000 |
| Motor Output | kW | 4 | 5,5 | 7.5 | 7.5 | 11 | 15 | 19 | 22 | 22 | 30 | 15 | 18,5 | 22 | 22 |
| Oil Tank Volume | Lt | 80 | 140 | 140 | 140 | 140 | 210 | 210 | 210 | 280 | 450 | 210 | 210 | 210 | 280 |
| Speeds (mm/s) | Approach | 160 | 150 | 150 | 160 | 160 | 160 | 150 | 130 | 110 | 80 | 170 | 160 | 150 | 120 |
| | Working | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 8 | 8 | 10 | 10 | 10 | 8 |
| | Return | 130 | 130 | 130 | 130 | 130 | 130 | 130 | 120 | 100 | 70 | 120 | 110 | 100 | 90 |
| Approx. Weight | Ton | 3.3 | 5.4 | 7.1 | 7.9 | 8.4 | 9.7 | 10 | 11 | 15 | 22 | 12 | 12.5 | 14 | 18.5 |
| Bending Length | A mm | 1250 | 2100 | 2600 | 3100 | 3100 | 3100 | 3100 | 3100 | 3100 | 3100 | 4100 | 4100 | 4100 | 4100 |
| Inside Frames | B mm | 1070 | 1600 | 2050 | 2550 | 2550 | 2550 | 2550 | 2550 | 2550 | 2550 | 3550 | 3550 | 3550 | 3550 |
| Side Frame Width | C mm | 1470 | 1580 | 1580 | 1590 | 1590 | 1600 | 1600 | 1610 | 1815 | 2060 | 1600 | 1600 | 1610 | 1820 |
| Bed Height | G mm | 800 | 880 | 880 | 880 | 880 | 880 | 880 | 880 | 905 | 1005 | 880 | 880 | 880 | 980 |
| Daylight Opening | K mm | 455 | 475 | 540 | 530 | 540 | 540 | 530 | 530 | 660 | 575 | 530 | 530 | 530 | 635 |
| Stroke | L mm | 215 | 210 | 260 | 260 | 260 | 260 | 260 | 260 | 320 | 320 | 260 | 260 | 260 | 320 |
| Table Width | M mm | 60 | 60 | 60 | 60 | 60 | 60 | 90 | 90 | 380 | 450 | 60 | 90 | 90 | 280 |
| Throat Gap | N mm | 410 | 410 | 410 | 410 | 410 | 410 | 410 | 410 | 500 | 500 | 410 | 410 | 410 | 500 |

- Design and specifications are subject to change without notice